

EMERGENCY AMENDED ORDINANCE

AN ORDINANCE AMENDING THE SUBDIVISION REGULATIONS OF WALTON COUNTY, FLORIDA, AS PROMULGATED IN ORDINANCE NO. 74-5 DATED AUGUST 20, 1974, PROVIDING FOR CHANGES IN ROADWAY BASE THICKNESS; PROVIDING AN EFFECTIVE DATE.

BE IT ORDAINED by the Board of County Commissioners of Walton County, Florida, that Section 16.24 of the Walton County Subdivision Regulations be amended to read as follows:

16.24 Roadway Base

Roadway base shall be constructed of sand-clay, sand asphalt, hot mix, soil cement*, limerock, limerock stabilized base, or shell stabilized base according to the specifications shown below. Upon approval of construction plans by the County Engineer, construction may begin, with testing of a six (6) inch minimum thickness, for all bases except sand asphalt hot mix, which shall have a four (4) inch minimum thickness, occurring as follows:

- Tests for subgrade bearing capacity and compaction shall be made by the County Engineer at intervals of no more than three hundred feet (300'), staggered to the left, right, and on the center line. Thickness of base shall be measured by the County Engineer at intervals of not less than three hundred feet (300') by means of holes drilled in the base, or at the time of test coring the surface course.
- Sand-Clay Base -- The material and construction shall conform to Florida DOT specifications as shown in Sections 240 and 912 of "Standard Specifications for Road and Bridge Construction."
- Sand Asphalt Hot Mix Base -- the material and construction shall conform to Florida DOT Specifications as shown in Section 335 of "Standard Specifications for Road and Bridge Construction."
- Soil Cement Base -- The material and construction shall conform to Florida DOT Specifications as shown in Section 270 of "Standard Specifications for Road and Bridge Construction."
- Compacted Limerock Base -- The material and construction shall conform to Florida DOT Specifications as shown in Sections 200 and 911 of "Standard Specifications for Road and Bridge Construction."
- Shell Stabilized Base -- The material and construction shall conform to Florida DOT Specifications as shown in Sections 260 and 913 of "Standard Specifications for Road and Bridge Construction."

*At the option of the County Engineer for special applications.

BE IT FURTHER ORDAINED by the Board of County Commissioners of Walton County, Florida, that all other provisions of said subdivision regulations not inconsistent herewith shall remain in full force and effect.

BE IT FURTHER ORDAINED by the Board of County Commissioners of Walton County, Florida, that this emergency ordinance shall take effect as provided by law.

PASSED this 9th day of January, 1979.

BOARD OF COUNTY COMMISSIONERS
OF WALTON COUNTY, FLORIDA

by James C. Rushing
James C. Rushing, Chairman

ATTEST:

Philip A. Anderson
Philip A. Anderson, Clerk